

DELFOR D97A

Version: November 2008 Final

Author: Cummins ECommerce
Modified: 11/14/2008

Table of Contents

Delivery Schedule Message 3

INTERCHANGE HEADER 6

MESSAGE HEADER 8

BEGINNING OF MESSAGE 9

DATE/TIME/PERIOD 10

REFERENCE 11

DATE/TIME/PERIOD 12

NAME AND ADDRESS 13

GENERAL INDICATOR 14

NAME AND ADDRESS 15

LINE ITEM 17

ITEM DESCRIPTION 18

PLACE/LOCATION IDENTIFICATION 19

REFERENCE 20

QUANTITY 21

DATE/TIME/PERIOD 22

REFERENCE 23

SCHEDULING CONDITIONS 24

QUANTITY 25

DATE/TIME/PERIOD 26

REFERENCE 27

MESSAGE TRAILER 28

INTERCHANGE TRAILER 29

DELFOR Delivery Schedule Message

Message Status=2

DELFOR is a delivery schedule message which is sent from Cummins, who is planning for the use or consumption of products, to a Trading Partner, who has to plan for the supply of the products. The DELFOR message gives the requirements regarding details for short term delivery and/or medium to long term scheduling of products. The scheduling can be used to authorize manufacturing and or the provision of materials. This is based on the terms and conditions defined in a purchase order or contract.

Not Defined:

<u>Pos</u>	<u>Tag</u>	<u>Segment Name</u>	<u>Status</u>	<u>Rep</u>	<u>Notes</u>	<u>Usage</u>
	UNB	INTERCHANGE HEADER	M	1		Must use
0010	UNH	MESSAGE HEADER	M	1		Used

Heading:

<u>Pos</u>	<u>Tag</u>	<u>Segment Name</u>	<u>Status</u>	<u>Rep</u>	<u>Notes</u>	<u>Usage</u>
0020	BGM	BEGINNING OF MESSAGE	M	1		Used
0030	DTM	DATE/TIME/PERIOD	M	10		Used
0050		Segment Group 1	C	10		Used
0060	RFF	REFERENCE	M	1		Must use
0070	DTM	DATE/TIME/PERIOD	C	1		Used
0080		Segment Group 2	C	99		Used
0090	NAD	NAME AND ADDRESS	M	1		Must use

Detail:

<u>Pos</u>	<u>Tag</u>	<u>Segment Name</u>	<u>Status</u>	<u>Rep</u>	<u>Notes</u>	<u>Usage</u>
0190		Segment Group 6	C	9999		Used
0200	GIS	GENERAL INDICATOR	M	1		Must use
0210		Segment Group 7	C	1		Used
0220	NAD	NAME AND ADDRESS	M	1		Must use
0370		Segment Group 12	C	9999		Used
0380	LIN	LINE ITEM	M	1		Must use
0400	IMD	ITEM DESCRIPTION	C	10		Used
0450	LOC	PLACE/LOCATION IDENTIFICATION	C	999		Used
0480		Segment Group 13	C	10		Used
0490	RFF	REFERENCE	M	1		Must use
0540		Segment Group 15	C	10		Used
0550	QTY	QUANTITY	M	1		Must use
0560	DTM	DATE/TIME/PERIOD	C	2		Used
0570		Segment Group 16	C	10		Used
0580	RFF	REFERENCE	M	1		Must use
0600		Segment Group 17	C	999		Used
0610	SCC	SCHEDULING CONDITIONS	M	1		Must use
0620		Segment Group 18	C	999		Used
0630	QTY	QUANTITY	M	1		Must use
0640	DTM	DATE/TIME/PERIOD	C	2		Used

<u>0650</u>		<u>Segment Group 19</u>	<u>C</u>	<u>10</u>	<u>Used</u>
0660	RFF	REFERENCE	M	1	Must use

Not Defined:

<u>Pos</u>	<u>Tag</u>	<u>Segment Name</u>	<u>Status</u>	<u>Rep</u>	<u>Notes</u>	<u>Usage</u>
1030	UNT	MESSAGE TRAILER	M	1		Used
	UNZ	INTERCHANGE TRAILER	M	1		Must use

Note:

Example EDI:
 UNB+UNOA:1+123456789:1+987654321:1+080901:2105+11
 UNH+1+DELFOR:D:97A:UN
 BGM+241+20080901-11111-0+5
 DTM+137:20080901:102
 DTM+158:20080831:102
 DTM+159:20090301:102
 NAD+SU+987654321::16++EXAMPLE SUPPLIER
 GIS+37
 NAD+ST+123456789::16++CUMMINS EXAMPLE DOC+REC LOC 001+COLUMBUS++47201
 LIN+1++11111:IN
 IMD+F++::ENGINE
 LOC+7+001
 RFF+ON:581000043
 QTY+48:1000:EA
 DTM+50:20080827:102
 QTY+3:5500:EA
 DTM+51:20080101:102
 DTM+52:20080901:102
 RFF+SI:1234567
 SCC+1++D
 QTY+1:2000
 DTM+2:20080905:102
 QTY+1:1000
 DTM+2:20080912:102
 QTY+1:1500
 DTM+2:20080919:102
 QTY+1:500
 DTM+2:20080926:102
 SCC+4++D
 QTY+1:1500
 DTM+2:20081003:102
 QTY+1:2000
 DTM+2:20081006:102
 QTY+1:2000
 DTM+2:20081013:102
 QTY+1:2000
 DTM+2:20081020:102
 QTY+1:1500
 DTM+2:20081027:102
 QTY+1:2000
 DTM+2:20081103:102
 QTY+1:2000
 DTM+2:20081110:102
 QTY+1:2500
 DTM+2:20081117:102
 QTY+1:2000

DTM+2:20081201:102
QTY+1:1500
DTM+2:20081208:102
QTY+1:3000
DTM+2:20081215:102
QTY+1:1500
DTM+2:20090105:102
QTY+1:2000
DTM+2:20090112:102
QTY+1:2000
UNT+66+1
UNZ+1+11

UNB INTERCHANGE HEADER

Pos:	Max: 1
Mandatory	
Group: N/A	Elements: 11

User Option (Usage): Must use

To head, identify, and specify an interchange.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UNB010	S001	SYNTAX IDENTIFIER	M	Comp		Must use
		Description: Identification of the agency controlling the syntax and indication of syntax level.				
	0001	Syntax identifier	M	a	4/4	Must use
		Description: Coded identification of the agency controlling a syntax and syntax level used in an interchange. All valid standard codes are used.				
	0002	Syntax version number	M	n	1/1	Must use
		Description: Version number of the syntax identified in the syntax identifier. All valid standard codes are used.				
UNB020	S002	INTERCHANGE SENDER	M	Comp		Must use
		Description: Identification of the sender of the interchange.				
	0004	Sender identification	M	an	1/35	Must use
		Description: Name or coded representation of the sender of a data interchange.				
	0007	Partner identification code qualifier	C	an	1/4	Used
		Description: Qualifier referring to the source of codes for the identifiers of interchanging partners. All valid standard codes are used.				
	0008	Address for reverse routing	C	an	1/14	Used
		Description: Address specified by the sender of an interchange to be included by the recipient in the response interchanges to facilitate internal routing.				
UNB030	S003	INTERCHANGE RECIPIENT	M	Comp		Must use
		Description: Identification of the recipient of the interchange.				
	0010	Recipient identification	M	an	1/35	Must use
		Description: Name or coded representation of the recipient of a data interchange.				
	0007	Partner identification code qualifier	C	an	1/4	Used
		Description: Qualifier referring to the source of codes for the identifiers of interchanging partners. All valid standard codes are used.				
	0014	Routing address	C	an	1/14	Used
		Description: Address specified by the recipient of an interchange to be included by the sender and used by the recipient for routing of received interchanges inside his organization.				
UNB040	S004	DATE/TIME OF PREPARATION	M	Comp		Must use

		Description: Date/time of preparation of the interchange.				
	0017	Date of preparation	M	n	6/6	Must use
		Description: Local date when an interchange or a functional group was prepared.				
	0019	Time of preparation	M	n	4/4	Must use
		Description: Local time of day when an interchange or a functional group was prepared.				
UNB050	0020	Interchange control reference	M	an	1/14	Must use
		Description: Unique reference assigned by the sender to an interchange.				
UNB060	S005	RECIPIENTS REFERENCE PASSWORD	C	Comp		Used
		Description: Reference or password as agreed between the communicating partners.				
	0022	Recipient's reference/password	M	an	1/14	Must use
		Description: Unique reference assigned by the recipient to the data interchange or a password to the recipient's system or to a third party network as specified in the partners interchange agreement.				
	0025	Recipient's reference/password qualifier	C	an	2/2	Used
		Description: Qualifier for the recipient's reference or password. All valid standard codes are used.				
UNB070	0026	Application reference	C	an	1/14	Used
		Description: Identification of the application area assigned by the sender, to which the messages in the interchange relate (the message identifier if all the messages in the interchange are of the same type).				
UNB080	0029	Processing priority code	C	a	1/1	Used
		Description: Code determined by the sender requesting processing priority for the interchange. All valid standard codes are used.				
UNB090	0031	Acknowledgement request	C	n	1/1	Used
		Description: Code determined by the sender for acknowledgement of the interchange. All valid standard codes are used.				
UNB100	0032	Cumunications agreement ID	C	an	1/35	Used
		Description: Identification by name or code of the type of agreement under which the interchange takes place.				
UNB110	0035	Test indicator	C	n	1/1	Used
		Description: Indication that the interchange is a test. All valid standard codes are used.				

Note:*Example EDI:*

UNB+UNOA:1+123456789:1+987654321:1+080901:2105+11

UNH MESSAGE HEADER

Pos: 0010	Max: 1
Mandatory	
Group: N/A	Elements: 2

User Option (Usage): Used

To head, identify, and specify a message.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UNH010	0062	Message reference number	M	an	1/14	Used
		Description: Unique message reference assigned by the sender.				
UNH020	S009	MESSAGE IDENTIFIER	M	Comp		Used
		Description: Identification of the type, version, etc. of the message being interchanged.				
	0065	Message type identifier	M	an	1/6	Used
		Description: Code identifying a type of message and assigned by its controlling agency.				
		<u>Code</u>		<u>Name</u>		
		DELFOR		Delivery schedule message		
	0052	Message type version number	M	an	1/3	Used
		Description: Version number of a message type.				
		<u>Code</u>		<u>Name</u>		
		D		Draft version		
	0054	Message type release number	M	an	1/3	Used
		Description: Release number within the current message type version number.				
		<u>Code</u>		<u>Name</u>		
		97A		Release 1997 - A		
	0051	Controlling agency	M	an	1/2	Used
		Description: Code identifying the agency controlling the specification, maintenance, and publication of the message type.				
		<u>Code</u>		<u>Name</u>		
		UN		UN/ECE/TRADE/WP.4, United Nations Standard Messages (UNSM)		

Note:

Example EDI:
UNH+1+DELFOR:D:97A:UN

BGM BEGINNING OF MESSAGE

Pos: 0020	Max: 1
Mandatory	
Group: N/A	Elements: 3

User Option (Usage): Used

A segment to indicate the type and function of a message and to transmit the identifying number.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BGM010	C002	DOCUMENT/MESSAGE NAME	C	Comp		Used
		Description: Identification of a type of document/message by code or name. Code preferred.				
	1001	Document/message name, coded	C	an	1/3	Used
		Description: Document/message identifier expressed in code.				
		<u>Code</u>		<u>Name</u>		
		241		Delivery schedule		
BGM020	C106	DOCUMENT/MESSAGE IDENTIFICATION	C	Comp		Used
		Description: Identification of a document/message by its number and eventually its version or revision.				
	1004	Document/message number	C	an	1/35	Used
		Description: Reference number assigned to the document/message by the issuer.				
BGM030	1225	Message function, coded	C	an	1/3	Used
		Description: Code indicating the function of the message.				
		<u>Code</u>		<u>Name</u>		
		4		Change		
		5		Replace		

Note:

Supplier needs to replace thier entire schedule when the replace code is utilized. The supplier needs to ensure their systems do not 'auto firm' the forecasted schedules.

Note:

Supplier may receive a change code for material during the week when a change to a part number occurs at Cummins. This will replace the entire schedule for the specific part number(s) listed.

Note:

*Example EDI:
BGM+241+20080901-11111-0+5*

DTM DATE/TIME/PERIOD

Pos: 0030	Max: 10
Mandatory	
Group: N/A	Elements: 1

User Option (Usage): Used

To specify date, and/or time, or period.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM010	C507	DATE/TIME/PERIOD	M	Comp		Used
Description: Date and/or time, or period relevant to the specified date/time/period type.						
	2005	Date/time/period qualifier	M	an	1/3	Used
Description: Code giving specific meaning to a date, time, or period.						
		<u>Code</u>		<u>Name</u>		
		137		Document/message date/time		
		158		Horizon start date		
		159		Horizon end date		
	2380	Date/time/period	C	an	1/35	Used
Description: The value of a date, a date and time, a time, or of a period in a specified representation.						
	2379	Date/time/period format qualifier	C	an	1/3	Used
Description: Specification of the representation of a date, a date and time, or of a period.						
		<u>Code</u>		<u>Name</u>		
		102		CCYYMMDD		

Note:

Example EDI:
 DTM+137:20080901:102
 DTM+158:20080831:102
 DTM+159:20090301:102

RFF REFERENCE

Pos: 0060	Max: 1
Mandatory	
Group: 1	Elements: 1

User Option (Usage): Must use

To specify a reference.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
RFF010	C506	REFERENCE	M	Comp		Used

Description: Identification of a reference.

1153		Reference qualifier	M	an	1/3	Used
------	--	---------------------	---	----	-----	------

Description: Code giving specific meaning to a reference segment or a reference number.

<u>Code</u>	<u>Name</u>
IP	Import licence number
LC	Letter of credit number

1154		Reference number	C	an	1/35	Used
------	--	------------------	---	----	------	------

Description: Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.

Note: *Import License Number or Letter of Credit Number.*

Note:

This segment is an optional feature that would only be used in certain international situations when an import license or letter of credit is needed to facilitate shipments to a particular country. In most instances, this segment will not be present.

Note:

*Example EDI:
RFF+LC:12345*

DTM DATE/TIME/PERIOD

Pos: 0070	Max: 1
Conditional	
Group: 1	Elements: 1

User Option (Usage): Used

To specify date, and/or time, or period.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM010	C507	DATE/TIME/PERIOD	M	Comp		Used
Description: Date and/or time, or period relevant to the specified date/time/period type.						
	2005	Date/time/period qualifier	M	an	1/3	Used
Description: Code giving specific meaning to a date, time or period.						
		<u>Code</u>		<u>Name</u>		
		125		Import licence date		
		137		Document/message date/time		
	2380	Date/time/period	C	an	1/35	Used
Description: The value of a date, a date and time, a time or of a period in a specified representation.						
Note: <i>Import License Date or Letter of Credit Date.</i>						
	2379	Date/time/period format qualifier	C	an	1/3	Used
Description: Specification of the representation of a date, a date and time or of a period.						
		<u>Code</u>		<u>Name</u>		
		102		CCYYMMDD		

Note:

Example EDI:
DTM+137:20080831:102

NAD NAME AND ADDRESS

Pos: 0090	Max: 1
Mandatory	
Group: 2	Elements: 3

User Option (Usage): Must use

To specify the name/address and their related function, either by CO82 only and/or unstructured by CO58 or structured by CO80 thru 3207.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
NAD010	3035	Party qualifier	M	an	1/3	Used
		Description: Code giving specific meaning to a party.				
		<u>Code</u>		<u>Name</u>		
		SU		Supplier		
NAD020	C082	PARTY IDENTIFICATION DETAILS	C	Comp		Used
		Description: Identification of a transaction party by code.				
	3039	Party id. identification	M	an	1/35	Used
		Description: Code identifying a party involved in a transaction.				
		Note: <i>Cummins will provide the correct number for use.</i>				
	3055	Code list responsible agency, coded	C	an	1/3	Used
		Description: Code identifying the agency responsible for a code list.				
		<u>Code</u>		<u>Name</u>		
		16		DUNS (Dun & Bradstreet)		
		92		Assigned by buyer or buyer's agent		
NAD040	C080	PARTY NAME	C	Comp		Used
		Description: Identification of a transaction party by name, one to five lines. Party name may be formatted.				
	3036	Party name	M	an	1/35	Used
		Description: Name of a party involved in a transaction.				

Note:

EDI Example:

NAD+SU+987654321::16++EXAMPLE SUPPLIER

GIS GENERAL INDICATOR

Pos: 0200	Max: 1
Mandatory	
Group: 6	Elements: 1

User Option (Usage): Must use

To transmit a processing indicator.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GIS010	C529	PROCESSING INDICATOR	M	Comp		Used

Description: Type of process indication.

7365	Processing indicator, coded	M	an	1/3	Used
------	-----------------------------	---	----	-----	------

Description: Identifies the value to be attributed to indicators required by the processing system.

Note: When BGM 1225 = 4, the value will be 36.

When BGM 1225 = 5, the value will be 37.

<u>Code</u>	<u>Name</u>
36	Changed information
37	Complete information

Note:

Example EDI:
GIS+37

NAD NAME AND ADDRESS

Pos: 0220	Max: 1
Mandatory	
Group: 7	Elements: 8

User Option (Usage): Must use

To specify the name/address and their related function, either by CO82 only and/or unstructured by CO58 or structured by CO80 thru 3207.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
NAD010	3035	Party qualifier	M	an	1/3	Used
		Description: Code giving specific meaning to a party.				
		<u>Code</u>		<u>Name</u>		
		BY		Buyer		
		ST		Ship to		
NAD020	C082	PARTY IDENTIFICATION DETAILS	C	Comp		Used
		Description: Identification of a transaction party by code.				
	3039	Party id. identification	M	an	1/35	Used
		Description: Code identifying a party involved in a transaction.				
		Note: <i>Cummins Plant DUNS number.</i>				
	3055	Code list responsible agency, coded	C	an	1/3	Used
		Description: Code identifying the agency responsible for a code list.				
		<u>Code</u>		<u>Name</u>		
		16		DUNS (Dun & Bradstreet)		
NAD040	C080	PARTY NAME	C	Comp		Used
		Description: Identification of a transaction party by name, one to five lines. Party name may be formatted.				
	3036	Party name	M	an	1/35	Used
		Description: Name of a party involved in a transaction.				
NAD050	C059	STREET	C	Comp		Used
		Description: Street address and/or PO Box number in a structured address: one to three lines.				
	3042	Street and number/p.o. box	M	an	1/35	Used
		Description: Street and number in plain language, or Post Office Box No.				
	3042	Street and number/p.o. box	C	an	1/35	Used
		Description: Street and number in plain language, or Post Office Box No.				
	3042	Street and number/p.o. box	C	an	1/35	Used
		Description: Street and number in plain language, or Post Office Box No.				
NAD060	3164	City name	C	an	1/35	Used
		Description: Name of a city (a town, a village) for addressing purposes.				

NAD070	3229	Country sub-entity identification	C	an	1/9	Used
		Description: Identification of the name of sub-entities (state, province) defined by appropriate governmental agencies.				
NAD080	3251	Postcode identification	C	an	1/9	Used
		Description: Code defining postal zones or addresses.				
NAD090	3207	Country, coded	C	an	1/3	Used
		Description: Identification of the name of a country or other geographical entity as specified in ISO 3166.				

Note:

For component part schedules, this NAD segment will identify the ship to location (element 3035 = ST) of the plant ordering the material.

For ship direct engine schedules, this NAD segment will identify the ordering/buying plant (element 3035 = BY).

Note:

Example EDI:

NAD+ST+123456789::16++CUMMINS EXAMPLE PLANT+EXAMPLE REC LOC 001+COLUMBUS++47201

LIN	LINE ITEM	Pos: 0380	Max: 1
		Mandatory	
		Group: 12	Elements: 2

User Option (Usage): Must use

To identify a line item and configuration.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN010	1082	Line item number	C	an	1/6	Used
Description: Serial number designating each separate item within a series of articles.						
Note: This is a sequential number that will begin with "1", and will be incremented by "1", for each LIN segment created.						
LIN030	C212	ITEM NUMBER IDENTIFICATION	C	Comp		Used
Description: Goods identification for a specified source.						
	7140	Item number	C	an	1/35	Used
Description: A number allocated to a group or item.						
Note: Cummins Part Number.						
	7143	Item number type, coded	C	an	1/3	Used
Description: Identification of the type of item number.						
		<u>Code</u>		<u>Name</u>		
		IN		Buyer's item number		

Note:
 Example EDI:
 LIN+1+++11111:IN

IMD ITEM DESCRIPTION

Pos: 0400	Max: 10
Conditional	
Group: 12	Elements: 2

User Option (Usage): Used

To describe an item in either an industry or free format.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IMD010	7077	Item description type, coded	C	an	1/3	Used
		Description: Code indicating the format of a description.				
		<u>Code</u>		<u>Name</u>		
		F		Free-form		
IMD030	C273	ITEM DESCRIPTION	C	Comp		Used
		Description: Description of an item.				
	7008	Item description	C	an	1/35	Used
		Description: Plain language description of articles or products.				

Note:

Example EDI:
 IMD+F+::ENGINE

LOC PLACE/LOCATION IDENTIFICATION

Pos: 0450	Max: 999
Conditional	
Group: 12	Elements: 2

User Option (Usage): Used

To identify a country/place/location/related location one/related location two.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LOC010	3227	Place/location qualifier	M	an	1/3	Used
Description: Code identifying the function of a location.						
		<u>Code</u>	<u>Name</u>			
		7	Place of delivery			
LOC020	C517	LOCATION IDENTIFICATION	C	Comp		Used
Description: Identification of a location by code or name.						
Note: Cummins uses the plant receiving location (dock).						
	3225	Place/location identification	C	an	1/25	Used
Description: Identification of the name of place/location, other than 3164 City name.						
Note: Cummins uses the Plant Receiving Location number (3 digit number).						

Note:

Example EDI:
LOC+7+001

RFF REFERENCE

Pos: 0490	Max: 1
Mandatory	
Group: 13	Elements: 1

User Option (Usage): Must use

To specify a reference.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
RFF010	C506	REFERENCE	M	Comp		Used

Description: Identification of a reference.

1153	Reference qualifier	M	an	1/3	Used
------	---------------------	---	----	-----	------

Description: Code giving specific meaning to a reference segment or a reference number.

<u>Code</u>	<u>Name</u>
ON	Order number (purchase)
AAL	Drawing number
AEQ	Drawing list number

1154	Reference number	C	an	1/35	Used
------	------------------	---	----	------	------

Description: Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.

Note: *If RFF 1153 = ON, this will be the Cummins Purchase Order Number.
 IF RFF 1153 = AAL, this will be the Cummins Drawing Number.
 If RFF 1153 = AEQ, this will be the Cummins Drawing Revision Number.*

Note:

*Example EDI:
 RFF+ON:12345*

QTY QUANTITY

Pos: 0550	Max: 1
Mandatory	
Group: 15	Elements: 1

User Option (Usage): Must use

To specify a pertinent quantity.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
QTY010	C186	QUANTITY DETAILS	M	Comp		Used
		Description: Quantity information in a transaction, qualified when relevant.				
	6063	Quantity qualifier	M	an	1/3	Used
		Description: Code giving specific meaning to a quantity.				
		<u>Code</u>		<u>Name</u>		
		3		Cumulative quantity		
		48		Received quantity		
	6060	Quantity	M	n	1/15	Used
		Description: Numeric value of a quantity.				
		Note: <i>If QTY 6063 = 3, the value will be the YTD quantity received.</i>				
		<i>If QTY 6063 = 48, the value will be the last receipt quantity.</i>				
	6411	Measure unit qualifier	C	an	1/3	Used
		Description: Indication of the unit of measurement in which weight (mass), capacity, length, area, volume or other quantity is expressed.				

Note:

Example EDI:
 QTY+48:1000:EA
 QTY+3:5500:EA

DTM DATE/TIME/PERIOD

Pos: 0560	Max: 2
Conditional	
Group: 15	Elements: 1

User Option (Usage): Used

To specify date, and/or time, or period.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM010	C507	DATE/TIME/PERIOD	M	Comp		Used
Description: Date and/or time, or period relevant to the specified date/time/period type.						
2005		Date/time/period qualifier	M	an	1/3	Used
Description: Code giving specific meaning to a date, time or period.						
		<u>Code</u>		<u>Name</u>		
		50		Goods receipt date/time		
		51		Cumulative quantity start date		
		52		Cumulative quantity end date		
2380		Date/time/period	C	an	1/35	Used
Description: The value of a date, a date and time, a time or of a period in a specified representation.						
Note: If DTM 2005 = 50, this value will be the Last Receipt Date.						
If DTM 2005 = 51, this value will the YTD Start Date.						
If DTM 2005 = 52, this value will be the YTD Stop Date.						
2379		Date/time/period format qualifier	C	an	1/3	Used
Description: Specification of the representation of a date, a date and time or of a period.						
		<u>Code</u>		<u>Name</u>		
		102		CCYYMMDD		

Note:

Example EDI:
 DTM+50:20080827:102
 DTM+51:20080101:102
 DTM+52:20080901:102

RFF REFERENCE

Pos: 0580	Max: 1
Mandatory	
Group: 16	Elements: 1

User Option (Usage): Must use

To specify a reference.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
RFF010	C506	REFERENCE	M	Comp		Used

Description: Identification of a reference.

1153		Reference qualifier	M	an	1/3	Used
------	--	---------------------	---	----	-----	------

Description: Code giving specific meaning to a reference segment or a reference number.

<u>Code</u>	<u>Name</u>
SI	SID (Shipper's identifying number for shipment)

1154		Reference number	C	an	1/35	Used
------	--	------------------	---	----	------	------

Description: Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.

Note: Last Shipment ID Number (SID) or Last Despatch Note Number.

Note:

Example EDI:
RFF+SI:1234567

SCC SCHEDULING CONDITIONS

Pos: 0610	Max: 1
Mandatory	
Group: 17	Elements: 2

User Option (Usage): Must use

To specify scheduling conditions.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SCC010	4017	Delivery plan status indicator, coded	M	an	1/3	Used
Description: Code indicating the level of commitment of schedule information.						
		<u>Code</u>	<u>Name</u>			
		1	Firm			
		4	Planning/forecast			
		10	Immediate			
		15	First time reported firm			
SCC030	C329	PATTERN DESCRIPTION	C	Comp		Used
Description: Shipment, delivery or production interval pattern and timing.						
	2013	Frequency, coded	C	an	1/3	Used
Description: Code specifying interval grouping of the delivery, production, etc. of the schedule.						
		<u>Code</u>	<u>Name</u>			
		D	Discrete			

Note:

Example EDI:
 SCC+1++D
 SCC+4++D

QTY QUANTITY

Pos: 0630	Max: 1
Mandatory	
Group: 18	Elements: 1

User Option (Usage): Must use

To specify a pertinent quantity.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
QTY010	C186	QUANTITY DETAILS	M	Comp		Used

Description: Quantity information in a transaction, qualified when relevant.

6063	Quantity qualifier	M	an	1/3	Used
------	---------------------------	---	----	-----	------

Description: Code giving specific meaning to a quantity.

<u>Code</u>	<u>Name</u>
1	Discrete quantity

6060	Quantity	M	n	1/15	Used
------	-----------------	---	---	------	------

Description: Numeric value of a quantity.

6411	Measure unit qualifier	C	an	1/3	Used
------	-------------------------------	---	----	-----	------

Description: Indication of the unit of measurement in which weight (mass), capacity, length, area, volume or other quantity is expressed.

Note: *The list of allowable codes is extensive. Some of the more commonly used codes are as follows:*

<u>Code</u>	<u>Name</u>
EA	Each
FT	Foot
GA	Gallon
KG	Kilogram
LB	Pound
LT	Liter
QT	Quart
PCE	Piece

Note:

*Example EDI:
QTY+1:2000*

DTM DATE/TIME/PERIOD

Pos: 0640	Max: 2
Conditional	
Group: 18	Elements: 1

User Option (Usage): Used

To specify date, and/or time, or period.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM010	C507	DATE/TIME/PERIOD	M	Comp		Used
Description: Date and/or time, or period relevant to the specified date/time/period type.						
2005		Date/time/period qualifier	M	an	1/3	Used
Description: Code giving specific meaning to a date, time or period.						
		<u>Code</u>		<u>Name</u>		
		2		Delivery date/time, requested		
2380		Date/time/period	C	an	1/35	Used
Description: The value of a date, a date and time, a time or of a period in a specified representation.						
Note: <i>Date Delivery Requested.</i>						
2379		Date/time/period format qualifier	C	an	1/3	Used
Description: Specification of the representation of a date, a date and time or of a period.						
		<u>Code</u>		<u>Name</u>		
		102		CCYYMMDD		

Note:

Example EDI:
DTM+2:20080905:102

RFF REFERENCE

Pos: 0660	Max: 1
Mandatory	
Group: 19	Elements: 1

User Option (Usage): Must use

To specify a reference.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
RFF010	C506	REFERENCE	M	Comp		Used
Description: Identification of a reference.						
	1153	Reference qualifier	M	an	1/3	Used
Description: Code giving specific meaning to a reference segment or a reference number.						
		<u>Code</u>		<u>Name</u>		
		RE		Release number		
	1154	Reference number	C	an	1/35	Used
Description: Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.						

Note:

This segment will only be used by those Cummins plants that require a release number assigned to each scheduled quantity and date.

Note:

*Example EDI:
RFF+RE:7654321*

UNT MESSAGE TRAILER

Pos: 1030	Max: 1
Mandatory	
Group: N/A	Elements: 2

User Option (Usage): Used

To end and check the completeness of a message.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UNT010	0074	Number of segments in a message	M	n	1/6	Used
		Description: Control count of number of segments in a message.				
UNT020	0062	Message reference number	M	an	1/14	Used
		Description: Unique message reference assigned by the sender.				

Note:

Example EDI:
UNT+66+1

UNZ INTERCHANGE TRAILER

Pos:	Max: 1
Mandatory	
Group: N/A	Elements: 2

User Option (Usage): Must use

To end and check the completeness of an interchange.

Element Summary:

<u>Ref</u>	<u>Tag</u>	<u>Element Name</u>	<u>Status</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
UNZ010	0036	Interchange control count	M	n	1/6	Must use
Description: Count either of the number of messages or, if used, of the number of functional groups in an interchange.						
UNZ020	0020	Interchange control reference	M	an	1/14	Must use
Description: Unique reference assigned by the sender to an interchange.						

Note:

Example EDI:
UNZ+1+11